Application of: Mitsuru TAKASHIMA

Serial No.: 10

10/018,676

Date Filed:

December 24, 2002

Page 2

This listing of claims will replace all prior listings of claims in the application:

1. (Previously Canceled)

2. (Currently Amended) A biomedical information collection apparatus, comprising:

(a) a plurality of closed compartments, spaced apart and made of an airtight flexible material, each of the closed compartments having a variable internal volume; a spring member placed inside of each of the closed compartments;

- (b) a plurality of closed air pressure sensors each including one or more of a nondirectional microphone and a pressure sensor, the closed air pressure sensors in communication with respective closed compartments for detecting and converting air pressure in each of the closed compartments into an electric signal; and
- (c) a plate-shaped member placed on the plurality of closed compartments <u>such that</u> when a living organism is placed on the plate-shaped member placed on the plurality of closed compartments while air remains in the closed compartments <u>and in</u> of the closed air pressure sensors, the air pressure in the closed compartments <u>being is</u> detected by <u>their the</u> respective non-directional microphones and <u>by the closed</u> pressure sensors <u>in communication with the closed compartments</u> to measure biomedical information including breath, heart rate, and body movements including a cough and a snore of the living organism.
- 3. (Currently Amended) The biomedical information collection apparatus according to claim 2, wherein the non-directional microphones and pressure sensors <u>in communication</u> with the closed compartments are mounted inside of each respective closed compartment.
- 4. (Previously Amended) The biomedical information collection apparatus according to claim 2, wherein the non-directional microphones and pressure sensors are mounted at an end portion of a hose connected to the closed compartments.
- (Currently Amended) A biomedical information collection apparatus, comprising:(a) a plurality of closed compartments, spaced apart and made of an airtight flexible

Application of: Mitsuru TAKASHIMA

Serial No.: 10/018,676

Date Filed: December 24, 2002

Page 3

material, each of the closed compartments having a variable internal volume; a spring member placed inside of each of the closed compartments;

(b) a plurality of closed air pressure sensors each including one or more of a nondirectional microphone and a pressure sensor, the closed air pressure sensors in communication with respective closed compartments for detecting and converting air pressure in each of the closed compartments into an electric signal; and

(c) a plate-shaped member placed on the plurality of closed compartments; ,such that when a living organism is placed on the plate-shaped member placed on the plurality of closed compartments while air remains in the closed compartments of and in the closed air pressure sensors, the air pressure in the closed compartments being is detected by their the respective non-directional microphones and by the pressure sensors to measure biomedical information including breath, heart rate, and body movements including a cough and a snore of the living organism;

wherein a microscopic pinhole is provided in each of the closed compartments to establish an air leak countermeasure to minimize an influence upon the non-directional microphones and pressure sensors.

Claims 6-13 (Previously Canceled).

- 14. (Previously Amended) The biomedical information collection apparatus according to claim 5, wherein the non-directional microphones and pressure sensors are mounted inside of each respective closed compartment.
- 15. (Previously Amended) The biomedical information collection apparatus according to claim 5, wherein the non-directional microphones and pressure sensors are mounted at an end portion of a hose connected to the closed compartments.